



## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: Textile Protector Waterbased (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Impregnation agents.

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Guardian Protection Products A/S

Address: Knudevejen 22

Zip code: 6600
City: Vejen
Country: DENMARK

Email: guardian@guardian.dk

Phone: +45 75471767 Fax: +45 75471787

#### 1.4. Emergency Telephone Number

+45 75 47 17 67 (Guardian Protection Products A/S)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

CLP-classification: Aerosol 3;H229

**Most serious harmful effects:** Pressurised container: May burst if heated. May cause slight irritation to the skin and eyes.

The product contains small quantities of organic solvents. When working in large areas in

poorly ventilated rooms, the vapours may cause headache and dizziness.

2.2. Label elements

Signal word: Warning

**Hazard Statements** 

H229 Pressurised container: May burst if heated.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

#### 2.3. Other hazards

The product does not contain any PBT or vPvB substances.

Endocrine disrupting properties: None known.





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

## SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Substance CAS No./ EC No./ REACH Reg. No.		Concentration	Notes	CLP-classification
Nitrogen	7727-37-9 231-783-9	5 - 10 %		Press. Gas ref. liq. gas;H281
2-(2- butoxyethoxy)ethanol 112-34-5 203-961-6		1 - 3 %	28	Eye Irrit. 2;H319
3-butoxypropan-2-ol	5131-66-8 225-878-4	1 - 3 %		Skin Irrit. 2;H315 Eye Irrit. 2;H319

Please see section 16 for the full text of H- / EUH-phrases.

28 = The substance is covered by regulation 1907/2006/EU, annex XVII regarding restrictions.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation:** Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical

advice in case of persistent discomfort.

Skin contact: Remove contaminated clothing. Wash skin with soap and water. Seek medical advice in

case of persistent discomfort.

**Eye contact:** Flush with water (preferably using eye wash equipment) until irritation subsides. Seek

medical advice if symptoms persist.

**Burns:** Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek

medical advice/transport to hospital. If possible, continue flushing until medical attention is

obtained.

**General:** When obtaining medical advice, show the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause slight irritation to the skin and eyes. Inhalation of vapours/spray mist may cause irritation to the upper airways. The product contains small quantities of organic solvents. When working in large areas in poorly ventilated rooms, the vapours may cause headache and dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam or water mist. Use water or water mist to cool non-ignited

stock

Unsuitable extinguishing

media:

Do not use water stream, as it may spread the fire.

#### 5.2. Special hazards arising from the substance or mixture





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

CAUTION! Aerosol containers may explode. Heating will cause a rise in pressure in packaging with a risk of bursting. Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

#### 5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with chemical resistant gloves.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stay upwind/keep distance from source. Provide adequate ventilation. Smoking and naked

flames prohibited.

For emergency responders: In addition to the above: Normal protective clothing equivalent to EN 469 is recommended.

#### 6.2. Environmental precautions

Avoid unnecessary release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Wipe up drops and splashes with a cloth.

#### 6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Smoking and naked flames prohibited. Running water and eye wash equipment should be available. Wash hands before breaks, before using restroom facilities, and at the end of work.

#### 7.2. Conditions for safe storage, including any incompatibilities

To be stored safely out of reach of children and not together with food, feed, medicine and the like. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not store with the following: Strong acids/ Strong alkalis/ Strong oxidisers/ Strong reducing agents. Store frost-free.

#### 7.3. Specific end use(s)

None.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## Occupational exposure limit

Substance name	Time period	ppm	mg/m³	Fiber/cm3	Remarks	Notation
2-(2- butoxyethoxy) ethanol	8h	10	67.5			
2-(2- butoxyethoxy) ethanol	15m	15	101.2			





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

Measuring methods: Compliance with occupational exposure limits may be checked by occupational hygiene

measurements.

Legal basis: Commission Directive 2000/39/EC (Occupational Exposure Limits) as subsequently

amended. Last amended by Commission Directive 2019/1831/EU. Directive 2004/37/EC (Exposure to carcinogens or mutagens at work) as subsequently amended. Last amended by Directive 2024/869/EU. Directive 2009/148/EC (Exposure to asbestos at work) as

subsequently amended. Last amended by Directive 2023/2668/EU.

#### **PNEC**

2-(2-butoxyethoxy)ethano	ol, cas-no 112-34-5			
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	1.1 mg/l			
PNEC sediment (freshwater)	4.4 mg/kg			
PNEC aqua (marine water)	110 μg/l			
PNEC sediment (marine water)	440 μg/kg			
PNEC soil	320 µg/kg			
PNEC aqua (intermittent releases (fresh water))	11 mg/l			
3-butoxypropan-2-ol, cas	-no 5131-66-8			
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	0,525 mg/l			
PNEC aqua (marine water)	0,0525 mg/l			
PNEC aqua (intermittent releases)	5,25 mg/l			
PNEC STP (wastewater-treatment facilities)	10 mg/l			
PNEC sediment (freshwater)	2,36 mg/kg dw			
PNEC sediment (marine water)	0,236 mg/kg dw			
PNEC soil	0,16 mg/kg dw			

## **DNEL - workers**

2-(2-butoxyethoxy)ethanol, cas-no 112-34-5						
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note	
Inhalation DNEL (acute/short-term exposure - local effects)	101.2 mg/m³					
Inhalation DNEL (long-term exposure - local effects)	67.5 mg/m³					
3-butoxypropan-2-ol,	cas-no 5131-66-8					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note	
Dermal DNEL (long- term exposure - systemic effects)	52 mg/kg bw/day					





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025

						V C I SIOI I. I.O.	
Inhalation DNEL (long-term exposure - systemic effects)	147 mg/m³						
DNEL - general po	pulation						
2-(2-butoxyethoxy)et	hanol, cas-no	112-34	-5				
Exposure	Value	Э	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note	
Oral DNEL (long- term exposure - systemic effects)	6.25 mg/kg t	ow/day					
3-butoxypropan-2-ol,	cas-no 5131	-66-8					
Exposure	Value	Э	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note	
Dermal DNEL (long- term exposure - systemic effects)	22 mg/kg bw	ı/day					
Inhalation DNEL (long-term exposure - systemic effects)	43 mg/m³						
Oral DNEL (long- term exposure - systemic effects)	12,5 g/kg bw	ı/day					
8.2. Exposure cor	ntrols						
Appropriate engine controls:	ering		e product under well-veed below.	entilated conditions. V	Wear the personal pro	tective equipment	
Personal protective eye/face protection:		Wear s 16321.	afety goggles if there	is a risk of eye splash	ı. Eye protection must	conform to EN	
hand protection:		In the event of direct skin contact, wear protective gloves: Type of material: Nitrile rubber. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374. The suitability and durability of a glove is dependant on usage, e.g. frequency and duration of contact, glove material thickness, functionality and chemical resistance. Always seek advice from the glove supplier.					
Personal protective respiratory protection		Light use (small volume, short term contact (below 10 min.)): Not required.  Medium use (medium volume, medium contact (below 2 hours)): Filter type: A/P.  Respiratory protection must conform to one of the following standards: EN 136/140/145.					

## **SECTION 9: Physical and chemical properties**

**Environmental exposure** 

controls:

## 9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Aerosol
Colour	Clear
Odour	Odourless
Solubility	Solubility in water: Complete

Ensure compliance with local regulations for emissions.

Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	No data	
Freezing point	No data	





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

		V 01010111 11010
Boiling point or initial boiling point and boiling range	100 °C	
Flammability	No data	
Flammability limits	No data	
Lower and upper explosion limit	No data	
Flash Point	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
pH (solution for use)	6.5	
pH (concentrate)	No data	
Kinematic viscosity	No data	
Viscosity	No data	
Partition coefficient n-octanol/water (log value)	No data	
Vapour pressure	No data	
Density	1 g/cm³	
relative density	No data	
Relative vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

#### 9.2. Other information

Parameter	Value/unit	Remarks
VOC (Volatile organic compounds):	<4%	

Other Information: None.

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with the following: Strong alkalis/ Strong oxidisers/ Strong reducing agents/ Strong acids.

## 10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

#### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid heating and contact with ignition sources. Avoid direct sunlight. Avoid temperatures >50°C.

#### 10.5. Incompatible materials

Strong alkalis/ Strong oxidisers/ Strong reducing agents/ Strong acids.

#### 10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity - oral





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

## 2-(2-butoxyethoxy)ethanol, cas-no 112-34-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		5660 mg/kg			

Ingestion of large quantities may cause discomfort. The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

#### Acute toxicity - dermal

#### 2-(2-butoxyethoxy)ethanol, cas-no 112-34-5

` •	• ,					
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		2700 mg/kg			

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation: The product does not have to be classified. Based on existing data, the classification

criteria are deemed not to have been met.

Skin corrosion/irritation: May cause slight irritation. The product does not have to be classified. Test data are not

available.

Serious eye damage/eye

irritation:

May cause eye irritation. The product does not have to be classified. Test data are not

available.

Respiratory sensitisation or

skin sensitisation:

The product does not have to be classified. Test data are not available.

**Germ cell mutagenicity:** The product does not have to be classified. Test data are not available.

**Carcinogenic properties:** The product does not have to be classified. Test data are not available.

**Reproductive toxicity:** The product does not have to be classified. Test data are not available.

**Single STOT exposure:** The product contains small quantities of organic solvents. When working in large areas in

poorly ventilated rooms, the vapours may cause headache and dizziness. Inhalation of vapours/spray mist may cause irritation to the upper airways. The product does not have to

be classified. Test data are not available.

**Repeated STOT exposure:** The product does not have to be classified. Test data are not available.

**Aspiration hazard:** The product does not have to be classified. Test data are not available.

#### 11.2. Information on other hazards

Endocrine disrupting

properties:

None known.

Other toxicological effects: None known.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### 2-(2-butoxyethoxy)ethanol, cas-no 112-34-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish			96hLC50	1300 mg/l			
Crustacea	Daphnia sp.		48hEC50	> 100 mg/l			
Algae			IC50	53 mg/l			

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

### 12.2. Persistence and degradability

#### 2-(2-butoxyethoxy)ethanol, cas-no 112-34-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
				89 %	Readily biodegradable.	OECD 301 C	

Expected to be biodegradable.

#### 12.3. Bioaccumulative potential

### 2-(2-butoxyethoxy)ethanol, cas-no 112-34-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
			BCF	2.9			
			Log Kow	0.68			

No bioaccumulation expected.

#### 12.4. Mobility in soil

Test data are not available.

#### 12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

#### 12.6. Endocrine disrupting properties

None known.

## 12.7. Other adverse effects

None known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Avoid unnecessary release to the environment.

Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility.

#### Aerosol sprays:

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

Absorbent/cloth contaminated with the product:

15 02 02\* absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by hazardous substances

## **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1. UN number or ID number: 1950 14.4. Packing group:

**14.2. UN proper shipping** AEROSOLS **14.5. Environmental** The product should not be

name: hazards: labelled as an

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

2.2

Hazard label(s): 2.2





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

Hazard identification number: **Tunnel restriction code:** Ε

Inland water ways transport (ADN)

14.1. UN number or ID number: 1950

14.2. UN proper shipping

name:

**AEROSOLS** 

14.4. Packing group:

14.5. Environmental

hazards:

The product should not be

The product is not a Marine

labelled as an

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

2.2

2.2

Hazard label(s): Transport in tank vessels:

Not applicable.

Sea transport (IMDG)

**14.1. UN number or ID number:** 1950

14.2. UN proper shipping

name:

14.3. Transport hazard

class(es):

Hazard label(s):

EmS:

**AEROSOLS** 

2.2

2.2

F-D, S-U

14.4. Packing group:

14.5. Environmental

hazards:

**Environmental Hazardous** 

Substance Name(s):

**IMDG Code segregation** 

group:

- None -

Pollutant (MP).

Air transport (ICAO-TI / IATA-DGR)

14.1. UN number or ID number: 1950

14.2. UN proper shipping

name:

AEROSOLS, NON-

FLAMMABLE

14.4. Packing group:

14.5. Environmental

hazards.

The product should not be

labelled as an

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

Hazard label(s): 2.2

14.6. Special precautions for user

None.

14.7. Maritime transport in bulk according to IMO instruments

2.2

Not applicable.

**SECTION 15: Regulatory information** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Special Provisions:** None known.

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessment has not been performed.





## **Textile Protector Waterbased (Aerosol)**

Issued: 08/03/2025 Version: 1.0.0

## **SECTION 16: Other information**

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	08/03/2025	JST	

Abbreviations: DNEL: Derived No Effect Level

PBT: Persistent, Bioaccumulative and Toxic PNEC: Predicted No Effect Concentration STOT: Specific Target Organ Toxicity

UFI: Unique formula identifier.

vPvB: Very Persistent and Very Bioaccumulative

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on

our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as

subsequently changed.

**Training advice:** A thorough knowledge of this safety data sheet should be a prerequisite condition.

**Classification method:** Calculation based on the hazards of the known components.

**Hazard statements** 

H229 Pressurised container: May burst if heated.

H281 Contains refrigerated gas, may cause cryogenic burns or injury.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

SDS is prepared by

Company: Bureau Veritas Solutions Denmark A/S

Address: Oldenborggade 25-31

Zip code: 7000
City: Fredericia
Country: DENMARK

Email: solutions-dk@bureauveritas.com

Phone: +45 77 31 10 00 Homepage: www.bureauveritas.dk

Country: EU