

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Trade name:** BeeWax - for wood

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended uses:** Care product.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

**Company:** Guardian Protection Products A/S  
**Address:** Knudevejen 22  
**Zip code:** 6600  
**City:** Vejen  
**Country:** DENMARK  
**Email:** guardian@guardian.dk  
**Phone:** +45 75471767  
**Fax:** +45 75471787

#### 1.4. Emergency Telephone Number

+45 75 47 17 67 (Guardian Protection Products A/S)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**CLP-classification:** The product shall not be classified as hazardous according to the classification and labeling rules for substances and mixtures..

**Most serious harmful effects:** May cause slight irritation to the skin and eyes.

#### 2.2. Label elements

The product shall not be classified as hazardous according to the classification and labeling rules for substances and mixtures..

#### 2.3. Other hazards

Assessment to determine PBT and vPvB has not been made.  
Endocrine disrupting properties: None known.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes	CLP-classification
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1	40 - 60 %		
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7	15 - 25 %	4	Asp. Tox. 1;H304  LD50 (Acute toxicity - oral): > 5000 mg/kg bw

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2 01-2119471991-29	1 - 3 %	Flam. Liq. 3;H226 Asp. Tox. 1;H304 Aquatic Chronic 2;H411 EUH066
--	-------------------------------	---------	---

Please see section 16 for the full text of H- / EUH-phrases.

4 = H304 is not applicable due to the high viscosity of the product.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation:</b>	Seek fresh air.
<b>Ingestion:</b>	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
<b>Skin contact:</b>	Remove contaminated clothing. Wash the skin with water.
<b>Eye contact:</b>	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
<b>General:</b>	When obtaining medical advice, show the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause slight irritation to the skin and eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media:</b>	Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.
<b>Unsuitable extinguishing media:</b>	Do not use water stream, as it may spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Can generate harmful flue gases containing carbon monoxide in the event of fire.

#### 5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. If there is a risk of exposure to vapour and flue gases, a self-contained breathing apparatus must be worn.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Stop leak if this can be done without risk.

**For emergency responders:** In addition to the above: Normal protective clothing equivalent to EN 469 is recommended.

#### 6.2. Environmental precautions

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

Prevent spillage from entering drains and/or surface water.

### 6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers. Wipe up minor spills with a cloth.

### 6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Running water and eye wash equipment should be available. Wash hands before breaks, before using restroom facilities, and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

The product should be stored safely out of reach of children and not together with food, feed, medicine and the like. Do not store with the following: Strong acids/ Strong alkalis/ Strong oxidisers/ Strong oxidisers.  
Storage temperature: 0-50 °C.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Occupational exposure limit:** Contains no substances subject to reporting requirements.

**Measuring methods:** Compliance with occupational exposure limits may be checked by occupational hygiene measurements.

**Legal basis:** Commission Directive 2000/39/EC (Occupational Exposure Limits) as subsequently amended. Last amended by Commission Directive 2019/1831/EU. Directive 2004/37/EC (Exposure to carcinogens or mutagens at work) as subsequently amended. Last amended by Directive 2024/869/EU. Directive 2009/148/EC (Exposure to asbestos at work) as subsequently amended. Last amended by Directive 2023/2668/EU.

### DNEL - workers

Distillates (petroleum), hydrotreated light paraffinic, cas-no 64742-55-8					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	5,58 mg/m <sup>3</sup>				
Inhalation DNEL (long-term exposure - systemic effects)	2,73 mg/m <sup>3</sup>				
Dermal DNEL (long-term exposure - systemic effects)	970 µg/kg bw/day				

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

### DNEL - general population

Distillates (petroleum), hydrotreated light paraffinic, cas-no 64742-55-8					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	1,19 mg/m <sup>3</sup>				
Oral DNEL (long-term exposure - systemic effects)	740 µg/kg bw/day				

### 8.2. Exposure controls

**Appropriate engineering controls:** Use the product under well-ventilated conditions. Wear the personal protective equipment specified below.

**Personal protective equipment, eye/face protection:** Not required.

**Personal protective equipment, skin protection:** Not required.

**Personal protective equipment, hand protection:** Plastic or rubber gloves recommended. The suitability and durability of a glove is dependant on usage, e.g. frequency and duration of contact, glove material thickness, functionality and chemical resistance. Always seek advice from the glove supplier.

**Personal protective equipment, respiratory protection:** Not required.

**Environmental exposure controls:** Ensure compliance with local regulations for emissions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Parameter	Value/unit	
State	Paste	
Colour	Yellow	
Odour	Sweet	
Solubility	Solubility in water: Insoluble	
Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	No data	
Freezing point	No data	
Boiling point or initial boiling point and boiling range	No data	
Flammability	No data	
Flammability limits	No data	
Lower and upper explosion limit	No data	
Flash Point	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
pH (solution for use)	No data	
pH (concentrate)	No data	
Kinematic viscosity	No data	
Viscosity	No data	

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

Partition coefficient n-octanol/water (log value)	No data	
Vapour pressure	No data	
Density	No data	
relative density	No data	
Relative vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

### 9.2. Other information

Parameter	Value/unit	Remarks
VOC (Volatile organic compounds):	0%	

**Other Information:** None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with the following: Strong oxidisers/ Strong reducing agents/ Strong alkalis/ Strong acids.

### 10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong oxidisers/ Strong reducing agents/ Strong alkalis/ Strong acids.

### 10.6. Hazardous decomposition products

None known.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity - oral

#### Distillates (petroleum), hydrotreated light paraffinic, cas-no 64742-55-8

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000 mg/kg bw			

Ingestion may cause discomfort. The product does not have to be classified. Test data are not available for all substances.

**Acute toxicity - dermal:** The product does not have to be classified. Test data are not available for all substances.

**Acute toxicity - inhalation:** The product does not have to be classified. Test data are not available for all substances.

**Skin corrosion/irritation:** May cause slight irritation. The product does not have to be classified. Test data are not available.

**Serious eye damage/eye** Temporary irritation. The product does not have to be classified. Test data are not available.

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

### irritation:

**Respiratory sensitisation or skin sensitisation:** The product does not have to be classified. Test data are not available.

**Germ cell mutagenicity:** The product does not have to be classified. Test data are not available.

**Carcinogenic properties:** The product does not have to be classified. Test data are not available.

**Reproductive toxicity:** The product does not have to be classified. Test data are not available.

**Single STOT exposure:** The product does not have to be classified. Test data are not available.

**Repeated STOT exposure:** The product does not have to be classified. Test data are not available.

**Aspiration hazard:** The product does not have to be classified. Test data are not available.

### 11.2. Information on other hazards

**Endocrine disrupting properties:** None known.

**Other toxicological effects:** None known.

## SECTION 12: Ecological information

### 12.1. Toxicity

The product does not have to be classified. Test data are not available.

### 12.2. Persistence and degradability

#### Distillates (petroleum), hydrotreated light paraffinic, cas-no 64742-55-8

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.	CEC L-33-A-93	

Test data are not available.

### 12.3. Bioaccumulative potential

Test data are not available.

### 12.4. Mobility in soil

Test data are not available.

### 12.5. Results of PBT and vPvB assessment

No assessment has been made.

### 12.6. Endocrine disrupting properties

None known.

### 12.7. Other adverse effects

None known.

## SECTION 13: Disposal considerations

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

### 13.1. Waste treatment methods

Avoid discharge to drain or surface water. If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste (Dir. 2008/98/EU). Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements. Empty, cleansed packaging should be disposed of for recycling. Uncleansed packaging is to be disposed of via the local waste-removal scheme.

EWC code: Depends on line of business and use, for instance 16 05 09 discarded chemicals other than those mentioned in 16 05 06, 16 05 07 or 16 05 08

Absorbent/cloth contaminated with the product: 15 02 03 absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02

### SECTION 14: Transport information

**14.1. UN number or ID number:** Not applicable.

**14.4. Packing group:** Not applicable.

**14.2. UN proper shipping name:** Not applicable.

**14.5. Environmental hazards:** Not applicable.

**14.3. Transport hazard class(es):** Not applicable.

### 14.6. Special precautions for user

None.

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Special Provisions:

None known.

#### 15.2. Chemical Safety Assessment

REACH Reg. No.	Substance name
01-2119471991-29	hydrocarbons, C10-C12, isoalkanes, <2% aromatics

**Other Information:** Chemical safety assessment has not been performed.

### SECTION 16: Other information

#### Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	08/03/2025	SUJ	

##### Abbreviations:

PBT: Persistent, Bioaccumulative and Toxic  
vPvB: Very Persistent and Very Bioaccumulative  
STOT: Specific Target Organ Toxicity

##### Other Information:

This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

# Safety Data Sheet

## BeeWax - for wood

Issued: 08/03/2025  
Version: 1.0.0

**Training advice:** A thorough knowledge of this safety data sheet should be a prerequisite condition.

**Classification method:** Calculation based on the hazards of the known components.

### Hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H411 Toxic to aquatic life with long lasting effects.

### Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

### SDS is prepared by

Company: Bureau Veritas Solutions Denmark A/S  
Address: Oldenborggade 25-31  
Zip code: 7000  
City: Fredericia  
Country: DENMARK  
Email: solutions-dk@bureauveritas.com  
Phone: +45 77 31 10 00  
Homepage: www.bureauveritas.dk

**Country:** EU